













FIBER FILM - PLAN DE SÉLECTION DE PRODUIT											
APPLICATION TYPE	INFORMATIONS SUR LES APPLICATIONS		TYPE DE CHARGE								
			TYPE A 			TYPE B 			TYPE C 		
											
			moins de 400 kg	> 400kg	> 800kg	moins de 400kg	> 400kg	> 800kg	moins de 400kg	> 400kg	> 800kg
MANUAL [MANUEL]	MAIN		FF MANUAL-L	FF MANUAL-GP	FF MANUAL-GP	FF MANUAL-L	FF MANUAL-GP	FF MANUAL-HD	FF MANUAL-GP	FF MANUAL-HD	
					FF MANUAL-HD		FF MANUAL-HD				
MACHINE	Tension à frein		FF ALPHA-L	FF ALPHA-L	FF ALPHA-GP	FF ALPHA-GP	FF ALPHA-GP	FF ALPHA-HD	FF ALPHA-HD	FF ALPHA-HD	
	SYSTÈME DE PRÉETIREMENT	Préétirement jusqu'à 180%	FF BETA-L	FF BETA-GP	FF BETA-HD	FF BETA-L	FF BETA-GP	FF BETA-HD	Les charges de TYPE C ne sont généralement pas emballées sur ce type de machine d'emballage		
		Préétirement jusqu'à 250%	Normal Machines	FF GAMMA-L	FF GAMMA-GP	FF GAMMA-HD	FF GAMMA-L	FF GAMMA-GP			
		Préétirement jusqu'à 350%	Avancé Machines (haute vitesse)	FF DELTA-L	FF DELTA-L	FF DELTA-L	FF DELTA-GP	FF DELTA-GP	FF DELTA-GP or HD	FF DELTA-HD	FF DELTA-HD